

LOW ZINC INDUSTRIAL HYDRAULIC OIL ADDITIVE PACKAGE T55031

●Introduction

It is mainly composed of high-grade ashless antioxidant and basic zinc containing antioxidant and anticorrosion additives, with high efficiency rust inhibitor additives, antiwear additives. Imported antifoam and demulsifier are blended as auxiliary additives. The blended hydraulic oil has excellent oxidation stability, inhibits the formation of oil sludge and prolongs the service life of the oil. The super strong anti-wear performance endows the metal with strong anti-corrosion protection, good sealing compatibility, and prolongs the service life of hydraulic component.

●Recommended Treat Rate (wt%): 0.6

●Specifications

Item	Typical Value	Test Method
Appearance	Yellow Transparent Liquid	Visual
Kinematic Viscosity (100°C), mm ² /s	Report	GB/T 265
Flash Point (COC), °C	>110	GB/T 3536
Sulfur, wt%	6.5	ASTM D5185
Phosphorus, wt%	3.2	ASTM D5185
Zinc, wt%	3.9	ASTM D5185

●Package, Handle & Storage

1. Packed in 200L metal drum, IBC-Tank or made to order.
2. Long term storage temperature should not exceed 45°C.
3. Handle & blending temperature should not exceed 65°C.
4. Not dangerous chemical, store in dry & clean warehouse.